

I claim:

1. A control system for a printing machine having at least one machine element, the control system comprising:

a central data processing unit;

5 an electronic machine controller connected to and controlled by said central data processing unit;

at least one controlled machine element of the printing machine connected to and controlled by said electronic machine controller;

10 a data carrier, an input device, and an output device connected to said central data processing unit;

said data carrier storing at least one data file for playing back instructions associated with at least one machine element, one machine function, and/or a functional or setting

15 error; and

wherein the at least one data file is activatable via said central unit such that, upon activation of the file, the instructions are played back via the output device.

20 2. The system according to claim 1, wherein said data carrier is a memory device of said central data processing unit.

3. The system according to claim 1, wherein the instructions are selected from the group consisting of optical and acoustical help instructions, and said output device is
5 selected from the group consisting of optical and acoustical output devices.

4. The printing machine of claim 1, wherein the data file is selected from the group consisting of audio, video, HTML, and
10 image files.

5. The printing machine according to claim 1, wherein said output device is selected from the group consisting of screen display and speaker.
15

6. The printing machine according to claim 1, wherein the input device is selected from the group consisting of touch-sensitive and light-sensitive input devices.

20 7. The printing machine according to claim 1, wherein the input device is selected from the group consisting of a screen, a film, a keyboard, and a sensor.

8. The printing machine according to claim 1, wherein the
25 files are activatable before, during, and after a setting of the machine controller.

9. The printing machine according to claim 1, wherein said central unit is programmed to activate a particular associated file in the event of a functional or setting error of a machine element or a machine function.

10. The printing machine according to claim 1, wherein said central unit is programmed to automatically activate a particular associated file in the event of a functional or setting error of a machine element or a machine function.

11. The printing machine according to claim 1, wherein said central unit is configured to recognize errors in the machine controller, to detect an error of a machine element, and to activate the particular associated file.

12. The printing machine according to claim 11, wherein said central unit is configured to detect functional errors and setting errors of the machine element.

13. A method of controlling a printing machine having an electronic machine controller and at least one machine element connected to the controller, the method which comprises:

inputting configuration data and adjusting a setting of the machine controller;

checking the setting for errors with a central unit, and determining, with an error recognition procedure, whether an erroneous setting is present and associating the setting to a given machine function or machine element; and

5 if an erroneous setting is present, activating a file associated with the machine function or the machine element by the central unit.

10 14. The method according to claim 13, wherein the error recognition procedure is a software procedure in the central unit.

15 15. The method according to claim 13, which comprises, when an erroneous setting is detected, automatically forwarding a signal to the central unit, and thereupon activating, with the central unit, the file associated with the applicable machine function or machine element.

20 16. The method according to claim 13, which comprises forwarding with input means upon actuation a signal to the central unit; thereupon checking with the central unit a machine status for active machine functions or machine elements, and activating a respectively file associated therewith.

25

17. The method according to claim 13, which comprises effecting an input under menu control via an input device.

18. The method according to claim 17, wherein the input
5 device is a screen display.

10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990